

100M KVM EXTENDER MANUAL

Industrial Products

Information Release Screen Splicing

Video Conference Teaching Projection

We reserve the copyright have product details, if the parameters and a minor change and appearance from time to tome, the factory specifications shall prevail, the company reserves final interpretation

@ 2013. all rights reserved

Product Introduction

KVM Extender is one of our independent development products. The newest promoted KVM Extender has high quality of imagine, remote keyboard and mouse action does not have the time delay. It may widely apply in the computer, monitor, security, multimedia teaching systems and so on. It could extend keyboard, mouse and video ports on computer up to 100m.It promotes the function of anti-thunder and antijamming to make sure the security and stability.

Features And Benefits

- 1.It can extend the power switch of the computer, keyboard, mouse and video port max of 100m
- 2.It can be switched from remote monitor to local monitor or switched from local monitor to remote monitor by the keystroke on the Sender or SCROLL on the local keyboard
- 3.Use the single cable (CAT5,CAT5E,CAT6), the cost is inexpensive
- 4.It supports (USB and PS/2 port) keyboard and mouse, it supports (VGA) port monitor
- 5.It can remove and insert the local and remote keyboard and mouse
- 6.Power on computer use the emulational keyboard and mouse
- 7.It supports DOS, Windows, Linux, Unix system
- 8.It does not need a driver, it is simple to install
- 9.The remote keyboard and mouse display is in real-time
- 10.The anti-jamming is strong
- 11.The anti-lightning and anti-invasion is strong Cascade operation for increasing the distance
- 12.Index of anti-lightning and anti-invasion: withstand air-discharge 15KV, contiguity-discharge 8KV


Parameter

input connector	1-ch VGA+ 1-ch USB
output connector	VGA, 2-PS2
local output	HD15PIN (VGA)
The best resolution	1024x768
bandwidth	350MHZ
input level range	0.5-2.0Vp-p
input level error	less than 3mV
input impedance	75Ω
output impedance	75Ω
echo ullage	-30dB@5MHz
Max DC compensation	±5mV-0
SNR	60dB
Connector standard	HDB15, USB, Mini-DIN6, RJ45, ps2
Video standard	VGA, SVGA, XGA, SXGA, UXGA, LCD
Cable standard	CAT5, CAT5E, CAT6 UTP
Power adapter	DC12V/1A
operational temperature	-25℃~+70℃
deposited temperature	-40℃~+80℃
relative humidity	0~95% (non-condensing)
MTBF	>30000 hours

Supplier Standard List

1. KVM extender transmitter receiver
2. 12V/1A power adapter
3. USB cable
4. the manual
5. factory maintenance card

Panel Description



Application Case

